United Nations ECE/TRANS/WP.29/2018/74

Economic and Social Council

Distr.: General
5 April 2018

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

175th session
Geneva, 19-22 June 2018
Item 14.3. of the provisional agenda
Consideration and vote by AC.3 of draft UN GTRs and/or draft amendments to established UN GTRs, if any: Proposal for Amendment 1 to UN GTR No. 19 (Evaporative Test emission procedures for the Worldwide harmonized Light vehicles Test Procedures (EVAP WLTP))

Technical report on the development of Amendment 1 to UN GTR No. 19 (Evaporative Test emission procedures for the Worldwide harmonized Light vehicles Test Procedures (EVAP WLTP))

Submitted by the expert from the European Commission*

The text reproduced below was prepared by the Informal Working Group (IWG) on Worldwide harmonized Light vehicles Test Procedure (WLTP) and was adopted by the Working Party on Pollution and Energy at its January 2018 session. This is the technical report, based on GRPE-76-06-Rev.1, submitted together with the proposal for Amendment 1 to UN GTR No. 19 on EVAP WLTP (ECE/TRANS/WP.29/2018/73).

* In accordance with the programme of work of the Inland Transport Committee for 2018–2019 (ECE/TRANS/274, para. 123 and ECE/TRANS/2018/21, Cluster 3.1), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

GE.18-05351(E)

1805351

Please recycle

Technical report on the development of Amendment 1 to UN GTR No. 19 (Evaporative Test emission procedures for the Worldwide harmonized Light vehicles Test Procedures (EVAP WLTP))

I. Introduction

1. During the seventy-fourth session of the Working Party on Pollution and Energy (GRPE) in January 2017, the Evaporative emission test procedure for the Worldwide harmonised Light vehicles Test Procedures (WLTP EVAP) Task Force (TF) submitted a working document and an informal document for the consideration of GRPE.

2. The working document ECE/TRANS/WP.29/GRPE/2017/3 (Proposal for a new UN Global Technical Regulation on Evaporative emission test procedure for the Worldwide harmonized Light vehicles Test Procedures), UN GTR No. 19, contained the new proposed test procedure to measure evaporative emission from non-sealed fuel tank systems.

3. Non-sealed fuel tank systems are mostly used in conventional vehicles with an internal combustion engine. Since these vehicles have a high chance of purging the fuel vapours inside the fuel tank systems and the canister(s) into the internal combustion engines, the pressure inside the fuel tank generated by fuel vapours is well maintained at low level.

4. From late 2016 to September 2017, thirteen meetings (including three face-to-face meetings and two drafting meetings) were held and the WLTP EVAP task force worked to include a test procedure covering the sealed fuel tank systems in UN GTR No. 19. These systems are expected to be used in the hybrid electric vehicles driven mainly by electric engines and in the future conventional vehicles.

5. Amendment 1 to UN GTR No. 19 complements the text of the UN GTR not only by adding descriptions of the test procedure for sealed fuel tank systems but also by adding other provisions related to non-sealed fuel tank systems which were raised along the discussions on sealed fuel tank systems.

6. The discussions of Amendment 1 were led by experts from Japan (Ms. Mayumi "Sophie" Morimoto) and the European Commission's Joint Research Center (Giorgio Martini). The drafting of the text was led by the expert from the European Commission (Serge Dubuc).

II. Sealed fuel tank systems - Test procedure development

A. Objectives

7. During parking events, the fuel temperature in the fuel tank system increases due to rising ambient temperature and solar radiation. As a result of the increased temperature and consequent evaporation of the fuel, as well as expansion of the air/fuel vapour mixture, the pressure inside the fuel tank system increases significantly. This may lead the evaporation of the lightest petroleum fractions with a corresponding increase of the pressure inside the fuel tank system. In non-sealed fuel tank systems, which are mostly used in conventional vehicles, the increase of the pressure inside the system is limited by the high probability of purging vapours inside the fuel tank system, and the pressure is vented mainly to the canister(s). The canister adsorbs and stores hydrocarbons (HC). However, this canister has a limited

adsorbing capacity (depending on several factors of which the most important are the carbon quality, mass, and fuel specification as well as the ambient temperature) and must be periodically purged to desorb the stored hydrocarbons. This occurs during vehicle driving events since part of the combustion air flows through the canister removing the adsorbed hydrocarbons which are then burned inside the engine.

8. Due to the potentially limited operation time of the combustion engine in hybrid electric vehicles, the use of sealed fuel tank systems is one of the alternative solutions to the system described above to control evaporative emissions. A sealed fuel tank system is by design a closed system that can store fuel vapours inside the system up to the fuel tank relief pressure. In this case, no fuel vapour is vented to the canister nor to the atmosphere. However, the sealed fuel tank systems must be depressurised. This depressurisation is generally achieved by opening a pressure relief valve before refuelling to ensure a safe operation. The mixture of air and vapours released through the pressure relief valve are stored in the canister(s) which are then purged when the combustion engine runs.

9. In the case of very hot temperature conditions, the pressure inside the fuel tank system might exceed the fuel tank relief pressure which is designed to avoid the risk of a rupture of the sealed fuel tank system.

10. A technological option to limit the pressure increase inside the sealed fuel tank system due to a rising ambient temperature is insulating the tank itself. This means that the temperature of the fuel will remain lower than the ambient temperature. This option has been taken into account when developing the test procedure.

B. Approach

11. The following points were discussed during WLTP EVAP task force meetings:

(a) Discussion points related to sealed fuel tank system test procedure

(i) Definitions and abbreviations

(ii) Test sequence – one continuous test or two separate tests (stand-alone puff loss test, and stand-alone hot soak loss and 48-hour diurnal test)

(iii) Fuel tank relief pressure requirement for sealed fuel tank system

(iv) Condition before puff loss loading to canister – soak temperature, soak duration, and pressure inside the fuel tank system after depressurisation

(v) Overflow puff loss emissions check after depressurisation

(vi) Condition of diurnal breathing loss test for sealed fuel tank system

(vii) Soak temperature

(b) Discussion points related to improvement of latest UN GTR No. 19

(i) Vehicle preparation – baking of tyres

(ii) Type approval authority witness

(iii) Butane Working Capacity (BWC) measurement

C. Amendments introduced in UN GTR No. 19

1. Sealed fuel tank system test procedure

1.1. Definitions and abbreviations

12. Definitions of "*NOVC-HEV*", "*HEV*" and "*HV*" were added using those from UN GTR No. 15.

13. Definition of "*Monolayer tank*" was updated and the term was renamed to "*Monolayer non-metal tank*".

14. Definition of "*Sealed fuel tank system*" was updated. Whether to include "*Semi-sealed fuel tank system*" which might release the vapours and the pressure from system on first day of diurnal phase but the pressure relief valve would not open for subsequent days was discussed. As not enough data was available, the task force decided to discuss it at the next stage.

15. Definition of "*Evaporative emissions*" was updated to include hydrocarbon vapours lost from the fuel system immediately before refuelling of a sealed fuel tank.

16. Definitions of "*Depressurisation puff loss*", "*Depressurisation puff loss overflow*", "*Fuel tank relief pressure*" and "*Auxiliary canister*" were newly added since these terms are related to sealed fuel tank system test procedure.

17. Definition of "*2 gram breakthrough*" was newly added to improve UN GTR No. 19.

18. The abbreviation for rechargeable electric energy storage system was newly added since this term is related to the sealed fuel tank system test procedure.

19. Some terms in definitions and abbreviations were decapitalised for drafting purpose.

1.2. Test sequence – one continuous test or two separate tests (stand-alone puff loss test, and stand-alone hot soak loss and 48-hour diurnal test)

20. The test procedure of sealed fuel tank systems consists of two parts. One is the determination of the volume of the depressurisation puff loss loaded to the canister immediately before refuelling and its overflow from the canister. The other is the stand-alone hot soak loss and 48-hour diurnal test, which are the same as for non-sealed fuel tank system.

21. A 2 gram breakthrough loading of the non-sealed tank system was replaced by the depressurisation puff loss loading volume for subsequent procedures which are the hot soak loss test and the 48-hour diurnal test.

22. Japan proposed to set separate test sequences to improve testing efficiency. On the other hand, some vehicle manufacturers indicated there are some systems which cannot separate canister(s) from system, and this requires a continuous one test sequence. With consideration of those systems, the task force decided to have both one continuous test procedure and two separate tests.

1.3. Fuel tank relief pressure requirement for sealed fuel tank system

23. JRC proposed to set a minimum requirement for fuel tank relief pressure. This proposal was based on concerns for vehicles which would pass the type approval test but might emit significant amount of vapours when the temperature rises above 35°C in the market. Some vehicle manufacturers and Japan opposed this proposal since this proposal may eliminate the possibility of new technologies such as insulated fuel tank systems. To solve the concerns of both, the task force determined to have 2 conditions for the temperature profile during the 48-hour diurnal test, one for systems with a fuel tank relief pressure equal

to or higher than 30kPa and another for those below 30kPa. This would provide manufacturers with the scope to develop systems which incorporate a wider range of new technologies.

24. The value of the fuel tank relief pressure to determine the condition of preparation was decided based on the study result provided by task force members. Their study was based on maximum monthly temperature of Rome, New Delhi and Kyoto. The study also included the estimation of the fuel tank pressure based on market fuel properties under the temperature condition of those cities. The task force decided to set 30kPa as a threshold by considering +5°C margin from maximum temperature.

1.4. Condition before puff loss loading to canister –soak temperature, soak duration, and pressure inside the fuel tank system after depressurisation

25. The soak temperature profile before puff loss loading to the canister was decided based on the 24-hour diurnal breathing loss test (DBL). After 11 hours, the temperature inside the soak room will reach to the maximum during the DBL profile. Therefore, the task force decided to use 11 hours as soak duration.

26. The pressure inside the system after depressurisation was decided as maximum 2.5 kPa above ambient pressure in normal vehicle operation and use. This is based on the pressure requirement inside the fuel tank system during run loss test as defined by the United States Environmental Protection Agency.

1.5. Overflow puff loss emissions check after depressurisation

27. Immediately before refuelling, the sealed fuel tank system will be depressurised before the fuel cap is opened. When depressurised, the pressure will be relieved to atmosphere through the canister. To avoid unexpected escape of vapours with those pressures, Japan proposed to include a check of overflow vapours from the canister during the sealed fuel tank system test procedure. After extensive discussions, the task force supported the proposal.

1.6. Condition of diurnal breathing loss test for sealed fuel tank system

28. As explained in paragraph 1.3., the task force decided to have two conditions for the temperature profile during the 48-hour diurnal test depending on the fuel tank relief pressure. The systems with fuel tank relief pressure equal to or higher than 30kPa will use a 20 to 35°C temperature profile, the same as a non-sealed fuel tank system. On the other hand, the system with a pressure lower than 30kPa should have a 20 to 38°C profile. This profiie was decided based on estimated pressure of sealed fuel tank system at +5°C margin maximum temperature.

1.7. Soak temperature

29. Within UN GTR No. 19 there are two different types of soak which are undertaken at different temperatures. The soak which occurs before the dynamometer test should be carried at 23°C, because dynamometer test is also undertaken at 23°C. The soak that takes place prior to the following sequences are carried out at 20°C because these sequences start from 20°C.

(a) The diurnal test (for both non-sealed fuel tank system and sealed fuel tank system test procedures);

(b) The conditioning for puff loss loading (for sealed fuel tank system test procedure only);

(c) Fuel tank depressurisation (for sealed fuel tank system test procedure only).

30. However, there exists one exemption in the sealed fuel tank system test procedure. This is where the dynamometer test starts after soaking at 20°C (paragraph 6.6.1.12. followed by paragraph 6.5.6. of Annex 1 of Amendment 1 to UN GTR No. 19). After intensive discussion within TF members, they decided to skip another soak at 23°C because it would cause a burden to soak again for at least another 6 hours.

2. Discussion points related to improvement of latest GTR No. 19

2.1. Vehicle preparation – baking of tyres

31. During seventy-fourth session of GRPE, The European Tyre & Rubber Manufacturers' Association (ETRMA) proposed to clarify the baking temperature of tyres. Task force members studied many documents to set the appropriate temperature. Finally, the temperature of baking tyres was decided based on the description of "bake" in US Tier 3 preamble, which was 50 °C or higher.

2.2. Type approval authority witness

32. During seventy-fourth session of GRPE, the International Motor Vehicle Inspection Committee (CITA) pointed out that the description in paragraph 5.3.11. of Annex 1 of UN GTR No. 19 "The manufacturer shall provide the responsible authority a test report" might be misleading and could be interpreted to mean that there is no chance of witness of evaporative emission test. Also at nineteenth session of the Informal Working Group (IWG) on WLTP, Union Technique de l'Automobile, du motocycle et du Cycle (UTAC) pointed out the need for a clearer description of an audit or a witness test.

33. With much discussion between authorities and industry members, paragraph 5.3.11. of Annex 1 of UN GTR No. 19 (paragraph 8. of Annex 1 of Amendment 1 to UN GTR No. 19) was changed to delete the description pointed out by CITA. The description of an audit or a witness test raised by UTAC was decided not to be written in detail since how this should be done depends on each Contracting Party.

2.3. BWC measurement

34. Japan raised the concern that a result from measurement of BWC50 will never be used or submitted to an authority. After discussion within task force members, measurement of BWC50 was deleted from the test procedure. However, BWC300 measurement, which is used to decide evaporative emission family, remains and shall be done before certification test according to the procedure written in Amendment 1 to UN GTR No. 19.